

QUALITY PURIFIES.

QUALITY WORKS.

LANXESS
Energizing Chemistry

Lewabrane® Seawater RO Membrane Elements

The **Lewabrane® ROS** types are reverse osmosis (RO) spiral-wound elements for seawater desalination. The special chemistry of this membrane leads to higher cross-linking of the polyamide layer. This higher degree of polymerization improves the mechanical and chemical stability of the thin barrier layer, offering greater durability and more stable rejection of mixed ion salt solutions and organic periods.

The **Lewabrane® ROS** type product family is designed to meet and exceed the nominal performance standards for desalination and is offered in both high-rejection (HR) and high-flow (HF) product types. Three different sizes of the series are available: ROS400, ROS440, and ROS085. The RO elements ROS400, and ROS440 have a standard length of 40 inches (1,016 mm) and a diameter of

8 inches (201 mm) suitable for use within standard RO membrane equipment. The product family also includes a 4-inch (101-mm) RO element suitable for smaller applications. All 8-inch diameter elements meet today's industry standards for RO membrane surface area at 400 and 440 square feet per 8-inch by 40-inch element.

Seawater (S) High rejection (HR)/high flow (HF)	Permeate flow	Salt rejection	Membrane area	Feed spacer thickness	Dimensions
S085 HR 4040	5.2 m ³ /day 1,380 gpd	99.8%	7.9 m ² 85 ft ²	0.8 mm 31 mil	1,016/100/19 mm (OD) 40/3.9/0.75 inch
S400 HR	24.6 m ³ /day 6,500 gpd	99.8%	37.2 m ² 400 ft ²	0.8 mm 31 mil	1,016/201/29 mm 40/7.9/1.125 inch
S440 HR	27.3 m ³ /day 7,200 gpd	99.8%	40.9 m ² 440 ft ²	0.7 mm 28 mil	1,016/201/29 mm 40/7.9/1.125 inch
S085 HF 4040	7.2 m ³ /day 1,910 gpd	99.8%	7.9 m ² 85 ft ²	0.8 mm 31 mil	1,016/100/19 mm (OD) 40/3.9/0.75 inch
S400 HF	34.1 m ³ /day 9,000 gpd	99.8%	37.2 m ² 400 ft ²	0.8 mm 31 mil	1,016/201/29 mm 40/7.9/1.125 inch
S440 HF	37.5 m ³ /day 9,900 gpd	99.8%	40.9 m ² 440 ft ²	0.7 mm 28 mil	1,016/201/29 mm 40/7.9/1.125 inch

Test conditions: applied pressure 55.2 bar (800 psi), NaCl concentration 32,000 mg/l, 25°C (77°F), pH 8, and recovery rate 8%.

Key attributes of the Lewabrane® RO SHR type

- Low salt passage
- More stable salt rejection during operating lifetime
- High rejection of critical ions

Key attributes of the Lewabrane® RO SHF type

- High flow productivity
- Low salt passage at high fluxes
- Low energy demand

Applications

The Lewabrane® RO SHR type was designed for single-pass seawater desalination plants where high rejection is necessary, while the Lewabrane® RO SHF type was developed for double-pass desalination plants where low energy consumption is demanded. Of course, both types can be installed in one pressure vessel as a hybrid system to improve rejection and energy demand.

Service and support

With the LewaPlus® design software, LANXESS offers a comprehensive software design tool for RO membrane and ion exchange resin (IX) systems, which is available in several languages. It combines the Lewabrane® RO membrane design with the existing Lewatit® ion exchange resin design, allowing the designer to move seamlessly from RO design to ion exchange design all within the same design software. For seawater applications, it offers different energy recovery devices, the design of a split partial system, and the calculation of a hybrid installation in the pressure vessel. LewaPlus® can design more than 5,000 possible configurations and offers a post-treatment and a cost-energy calculation tool.

Contact

LANXESS Deutschland GmbH
Liquid Purification Technologies
Kennedyplatz 1
50569 Cologne, Germany
Phone: +49 221 88850
E-mail: lewabrane@lanxess.com

We are happy to support your business. Please contact us for additional information: visit www.lpt.lanxess.com



LANXESS
Energizing Chemistry

Health and Safety Information: Appropriate literature has been assembled which provides information concerning the health and safety precautions that must be observed when handling the LANXESS products mentioned in this publication. For materials mentioned which are not LANXESS products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be followed. Before working with any of these products, you must read and become familiar with the available information on their hazards, proper use and handling. This cannot be overemphasized. Information is available in several forms, e.g., material safety data sheets, product information and product labels. Consult your LANXESS representative in Germany or contact the Regulatory Affairs and Product Safety Department of LANXESS Deutschland GmbH or – for business in the USA – the LANXESS Corporation Product Safety and Regulatory Affairs Department in Pittsburgh, PA, USA.

Regulatory Compliance Information: Some of the end uses of the products described in this publication must comply with applicable regulations, such as the FDA, BfR, NSF, USDA, and CPSC. If you have any questions on the regulatory status of these products, contact – for business in the USA – the LANXESS Corporation Regulatory Affairs and Product Safety Department in Pittsburgh, PA, USA or for business outside US the Regulatory Affairs and Product Safety Department of LANXESS Deutschland GmbH in Germany.

The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information.

Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.

All trademarks are trademarks of the LANXESS Group, unless otherwise specified. Status 07/2017